

StaticWorx TriboShield Static Dissipative
Carpet Treatment

PRODUCT DESCRIPTION

StaticWorx TriboShield is specifically designed for use in maintenance programs whose goal is to reduce static electricity buildup. StaticWorx TriboShield may be used to increase the static control properties of surfaces in areas where sensitive electronic components are used. This product is equally effective on carpet, upholstery and fabrics. Environmentally safe, it is noncorrosive, nonflammable, and biodegradable.

APPLICATION & MAINTENANCE

Floor Surfaces should be vacuumed to remove loose dirt and soil. Remove stains and soil with spotter or shampooing procedure. Using a trigger or pressurized sprayer, deliver a fine mist of TriboShield to cover the application area evenly. Allow the carpet to dry before admitting foot traffic. For more frequent applications, the product may be diluted. Reapply as needed to control static, and after shampooing. Static control properties should last 30 to 90 days. Coverage is approximately 1000 square feet per gallon.

SAFETY INFORMATION

Health	1
Flammability	0
Reactivity	0
Personal Protection	B

CAUTION: May cause eye and skin irritation. Wear safety glasses and plastic gloves when handling material. Prolonged contact with skin may cause dermatitis. If ingested, drink milk, egg whites, gelatin solution, or large volumes of water. Do NOT induce vomiting. For eye or skin contact, flood with water. Contact a physician immediately.

Contains Diethylene Glycol Methyl Ether #111-77-3. For detailed information, consult MSDS sheet.

SPECIFICATIONS

Active ingredients	Anti-static and quaternary compounds
pH	6.5 - 7.5
Free Ammonia	None
Free Alkali	None
Free Acid	None
Phosphates	None
Abrasives	None
Color	Light Green
Odor	Mild
Solubility in Water	100%
Freeze/Thaw Stability	3 cycles
Shelf Life	Minimum 1 year at room temperature
Flash Point	None
Weight per Gallon	8.5
Biodegradable	Yes
Soil Suspension	Good